



Thermal Transfer Ribbons

US310

Resin

Flat Head

US310 is a flat head resin ribbon, designed to provide a durable image on to plastic labels. It is optimised for resistance to scratching and smudging.

RIBBON SPECIFICATION

RIBBON

GRADE : RESIN, FLAT-HEAD
COLOUR : BLACK
THICKNESS : 6.7±0.3 µm
Anti-static formulation ink
BASE FILM : POLYESTER (4.5±0.3 µm)
BACK COAT : SILICONE BASED
INK MELTING POINT : 75 °C

STORAGE AND USE

STORAGE : 0-40 °C (32-104 °F), 20-80 %RH
USE : 5-35 °C (41-95 °F) , 20-80 %RH

RECOMMENDED LABEL STOCK

Silver Matte, Synthetic Paper, PET, PVC

CERTIFICATIONS

HEAVY METALS : 2011/65/EU, (EU)2015/863 (RoHS, RoHS2.0)
REACH : SVHC free
ISEGA CERTIFIED : Regulation (EC) no.1935/2004
FDA
BPA

*Above documents are available upon request.

APPLICATION



NAMEPLATE



BARCODE




PHARMACEUTICAL



RIBBON PERFORMANCE

IMAGE DENSITY (KONICA MINOLTA FD-5)




SCRATCH /SMUDGE RESISTANCE (ANSI)




Pressure: 1.96x10⁴ Pa

Stroke Cycle: 3,000 cycles with corrugated paper

PRINT SPEED (mm/sec)



UV RESISTANCE (%)




168 hours exposed on UV test machine.

TRANSFER SENSITIVITY



SOLVENT RESISTANCE



* The numerical value indicated on this sheet is catalog value, and is not guarantee value.

* The information shown above is tentative and subject to change without notice.



UNION CHEMICAL Global Network

Japan : Union Chemicar Co., Ltd.

China (Shanghai) : Union Chemicar (Shanghai) Co., Ltd.

China (Tianjin) : Union Chemicar (Tianjin) Co., Ltd.

United States : Union Chemicar America Inc.

United Kingdom : Union Chemicar UK Limited

Netherlands : Union Chemicar Europe B.V.

Germany : Union Chemicar Deutschland GmbH

India : Union Chemicar India Pvt. Ltd.



[26 Jun. 2023]